Part number OKM 04





Male insert, CK series, screw terminal connection, 4 poles + PE, 10 A 230/400 V 4 kV 3, size "21.21"

| Product description | | Material properties | |
|---|---|--|--|
| Product type | Insert | Main material | Polycarbonate (PC) |
| Series | СК | Other materials | Contacts: copper alloy |
| Connection type | Screw terminal connection | | Gasket: NBR |
| Gender | Male | Colour | RAL 7032 grey |
| N. of poles | 4 poles + 🖨 | RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| Size | Size "21.21" | China RoHs - EFUP | 50 |
| Technical data | | | Yes |
| Current | 10 A | REACH SVHC substances | Lead |
| Voltage | 230 - 400 V | SCIP number | 1a9c93ff-0445-4a16-81e3-1609ac5274d6 |
| Rated impulse withstand voltage | 4 kV | Approvals / Standards | |
| Pollution degree | 3 | Reference standard | EN 61984:2009-06 |
| Rated voltage according to | | Certifications | CSA, CQC, DNV, BV, EAC |
| UL/CSA | 600 V | UL | ECBT2 |
| Wire cross-section | 0,75 mm² - 2,50 mm² | General ordering information | |
| AWG size | 18 - 14 | EAN13 code | 8015747028295 |
| Contact type | Turned silver plated | eCl@ss 8.1 | 27440205 |
| IP degree of protection | IP20 without enclosure, IP44/IP66/IP67/IP68/IP69 with enclosure | ETIM 7.0 | EC000438 |
| Further technical details | with enclosure | Packaging Information | |
| Characteristics according | | Packaging length | 210,00 mm |
| to EN 61984 | 10A 230/400V 4kV 3; 10A 400/690V 4kV 2 | Packaging height | 200,00 mm |
| Mating cycles | ≥ 500 | Packaging width | 130,00 mm |
| Insulation resistance | ≥ 10 GΩ | Packaging weight | 3,19 kg |
| Contact resistance | ≤ 2 mΩ | Packaging volume | 5,46 dm ³ |
| Weight | 14,50 g | Packaging description | Carton box |
| Operating temperature range (min, max) | -40°C +100°C | Packaging quantity Packaging EAN code | 200 Pcs 8015747028301 |
| Conductors stripping | | Sub-packaging length | 197,00 mm |
| length | 6 mm | Sub-packaging height | 35.00 mm |
| UL 94 flammability rating | V-1 | Sub-packaging width | 113,00 mm |
| Torque for main contact | M3: 0,5 Nm; 4,4 lb.in (0,5 x 3 mm) | Sub-packaging weight | 0,64 kg |
| Tightening torque for PE connection | M3: 0,5 Nm; 4,4 lb.in (0,5 x 3 mm) | Sub-packaging volume | 0,78 dm ³ |
| | | Sub-packaging description | Carton tray |
| Tightening torque for | M3: 0,5 Nm; 4,4 lb.in (Ph1 or 0,8 x 5,5 mm) | Sub-packaging quantity | 40 Pcs |
| fixing screws | | Sub-packaging EAN barcode | 8015747028318 |
| | | | |

Part number



Catalogue drawings



contacts side (front view)



Derating curves



Notes

Dimensions shown in mm are not binding and may be changed without notice.



California Proposition 65 Information



This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.